

How to measure guide



Sliding doors fitted to Trend® Synergy® and Quantum® FX sliding doors (Post Nov 2016)

To ensure the Prowler Proof ForceField® or Protec security screen doors you are ordering fit and perform perfectly, please follow the steps below. All doors should be ordered as make size. Please note all references should be taken from outside view looking in.

1

Drop

Left: _____ mm
Subtract 12mm
= _____ mm

Right: _____ mm
Subtract 12mm
= _____ mm

Note: Use smallest size for door opening size when ordering.

2

Interlock lengths

Use your door opening size (A) and subtract interlock clearance of 45mm: _____ mm

3

Width

Top: _____ mm
Add 32mm: _____ mm

Middle: _____ mm
Add 32mm: _____ mm

Bottom: _____ mm
Add 32mm: _____ mm

Note: *Allowances: 32mm (Subtract 6mm for striker and add 38mm for interlock allowance).

4

Diagonal

X. Top left to bottom right: _____ mm

Y. Top right to bottom left: _____ mm

X-Y= _____ mm

Note: This is out of diagonal dimension - max +/- 15mm.

5

Lock height

The security door's handle can be above or below the existing door's lock/handle.
Above: Measure from jamb to top of existing door's lock/handle: _____ mm
Add 25mm = _____ mm
Below: Measure from jamb to bottom of existing door's lock/handle: _____ mm
Subtract 185mm = _____ mm
Note: Select one position only.

6

Handle side

Left Hand Side

Right Hand Side

From the outside looking in, which side should the handle be on the door? ☐ Left ☐ Right
Note: Usually the same side as the handle on the existing door.

Customer details	
Customer name	
Contact number	
Address	

Designed and manufactured by Gershwin Pty Ltd ABN 22 064 102 816
122 Buchanan Road, PO Box 237, Banyo QLD 4014
P 07 3363 0666 | E info@prowlerproof.com.au
prowlerproof.com.au