How to measure guide

Sliding doors fitted to Trend® Synergy® and Quantum® FXX stacking doors (Post Nov 2016)

To ensure the Prowler Proof ForceField® or Protec security screen doors you are ordering fit and perform perfectly, please follow the steps below. All doors should be ordered as make size. Please note all references should be taken from outside view looking in.

1 Drop





Left: _____ mm
Subtract 12mm
= _____ mm

Right: ____ mm
Subtract 12mm
=_____ mm

Note: *Use smallest size for door opening size when ordering. Both screen doors will be this height.*

2 Interlock lengths

Use your door opening size (A) and subtract interlock clearance of 45mm: _____ mm

3 Width



Top:_____ mm
Add 92mm, then divide by 2:
_____ mm

Middle: _____ mm
Add 92mm, then divide by 2:
_____ mm

Bottom: _____ mm
Add 92mm, then divide by 2:
_____ mm

Note: *Both screen doors will be this width.*



Customer details

Customer name	
Contact number	
Address	

4 Optional bolts (*additional costs)

Required ☐ Yes ☐ No

Select Type ☐ Flush bolt ☐ Patio bolt

Position leading edge inactive leaf

☐ Top ☐ Bottom

5 Lock height



The security door's handle can be above or below the existing door's lock/handle.

Above: Measure from jamb to top of existing door's lock/handle:
_____ mm
Add 25mm = _____ mm

Below: Measure from jamb to bottom of existing door's lock/handle:_____ mm
Subtract 185mm = _____ mm

Note: *Select one position only.*

6 Handle side

Left Hand Side

Right Hand Side

From the outside looking in, which side should the handle be on the door?

☐ Left

Note: *Usually the same side as the handle on the existing door.*

☐ Right

Designed and manufactured by Gershwin Pty Ltd ABN 22 064 102 816
122 Buchanan Road, PO Box 237, Banyo QLD 4014
P 07 3363 0666 | **E** info@prowlerproof.com.au
prowlerproof.com.au